

Warmer, dryer, faster! An ingenious idea from the team at Blokart, the Pod quickly turns your kart into an all weather racing machine. Dust, dirt, sand, rain and snow are no longer an excuse to stay at home. Reduced wind resistance significantly improves performance and the improved comfort allows you to enjoy sailing longer.



Please follow the assembly instructions carefully to attach the Pod correctly.



Assembly Instructions

1. Set-up your Blokart, but do not insert the handlebar. Unpack the Pod, including the Skin, Windscreen, Footbar, Strap and Bungees.
2. Remove the front fork from the kart by undoing the quick-release clamp and retaining pin and slide the fork out.

3. Slip the Footbar under the keel tube and attach it with the quick-release clamp. Wrap the long bungee loop around the front of the keel as shown and while holding the plastic bead stretch the bungee around the fork tube to further hold the Footbar in place.



4. Slide the skin under the chassis. Locate the hole in the front of the skin with the fork tube but do not pull the skin over the Footbar yet.



5. Fit the Pod tension strap by looping the strap over the nose frame and threading the straps back through the loop as pictured.

6. Ensure the Pod Skin nose buckle is undone and pull the front of the skin over the Footbar and attach the Pod skin buckle through the loop in the strap but do not over-tighten.

7. Loop the remaining strap around the Mast Base above the tri-knobs, rethread the ladder-lock and tighten. This helps to stabilise the Pod Windscreen.

8. Replace the front fork and insert handle bar, ensuring the fork retaining pin is in place and the Quick Release Clamp is suitably tightened.

9. Remove the right axle and pass the right strap at the rear of the skin around the right side of the chassis as shown. Replace axle and then repeat process on the right side but do not tighten the rear ladder lock yet.



10. Raise the triangular panel at the rear of the Pod Skin ensuring it is on the outside of the strap across the back of the Pod, then thread the short bungee through the back of the webbing loop on top of the skin and hook over the pulley-whip socket, followed by the plastic bead over the pulley-whip socket. This will give good tension. Pull the plastic bead to one side for head clearance.

Note: When folding seat down with skin on, de-tension skin by unhooking only the plastic bead to prevent damage from over tensioning.



11. Lift up a side of the skin, and with a plastic bead threaded from front to back through the webbing loop, lift the bead and loop over the side strut and push the plastic bead under the foot bar from the outside and slide it toward the back of the kart to lock in



12. Repeat on other side, then lift bungee up and over mast base to tension both sides evenly and together.

13. Tighten the Pod skin for a neat fit by pulling the rear ladder lock strap behind the seat.

14. Carefully peel the protective plastic from both sides of the windscreen. Some prefer to leave the white film on the inside to preserve the screen for a while longer.

15. Attach the windscreen to the skin using Channel and bolt rope. Always ensure the Channel and the bolt rope on the skin are clean and free from sand and grit before fitting. A small amount of dry silicone lubricant may be used to aid with fitting. This should be applied to the inside of the channel rather than the skin.

16. Starting at the front of the kart, push the front wheel fully to one side so it is out of the way. Stand on front wheel to lay over to allow screen clearance and also restrain the chassis from rolling back when fitting the screen.



17. With the black trim and BK logo on the windscreen facing out, slide both sides of the channel on evenly and work your way up as smoothly as possible.

18. If / when it becomes difficult, lift the top of the screen up with one hand to straighten skin and use other to slide / bump the lid up with other hand at the nose. Fine adjustments can be made to the seating of the pod windscreen by pulling one side up at a time when nearing the top.

19. Fit your Pod Protector Bar (if you have one)..... and go sailing!

Important:

- Never fit the Pod windscreen upside down or roll the opposite to the way that it fits the Pod and never roll it lengthways. The Channels must remain straight at all times.
- The Pod windscreen is the same shape as the Blokart bag so pack the screen on top of your kart when transporting.
- Avoid scratching the Pod windscreen as scratches will be permanent.
- Capsizing on hard surfaces without a Pod Protector Bar will result in Pod damage.



Accessory Tip: Help protect the nose of your Pod with a "Pod Protector Bar"
Part # for ordering is XPD0353